


Cassette Selection Guide



| | MPO CASSETTES | | SPLICE CASSETTE |
|----------------------------|---------------------------------|---|------------------------------------|
| | PRECISIONFLEX® LGX MPO CASSETTE | PRECISIONFLEX® HIGH DENSITY MPO-LC CASSETTE | PRECISIONFLEX® FOX SPLICE CASSETTE |
| Part Number | Configurator Needed | PFCST-XX 1X12MPOM-LC-S | Configurator Needed |
| Fiber Type | SM & MM | SM & MM | SM & MM |
| Fiber Mode | Pre-Terminated | Pre-Terminated | 12ct Ribbon: 900um coated fiber |
| Fiber Count | 8F, 12F, 24F | 12F | 6F, 12F, 24F |
| Max LC Count per RU | 72F LC | 144F | 72F LC |
| Entry | MPO | MPO | Splice |
| Faceplate: Ports | 8, 12, 24 | 12 | 6, 12, 24 |
| Faceplate: Connector Type | LC, SC, FC, ST | LC | LC, SC, ST |
| ABF Suitable | Limited Applications | | (Recommended) |
| Hyperscale/AI DC Suitable | | | |
| DC/Central Office Suitable | | Limited Applications | |
| Mass Transit Suitable | Limited Applications | | |
| Corning CCH Compatible | Requires Adapter Panel | | Requires Adapter Panel |
| QR to Cut Sheet | View Cut Sheet | View Cut Sheet | View Cut Sheet |

To learn more information visit www.SumitomoElectricLightwave.com