

Safety Data Sheet

**Section 1: Identification of the Substance/Mixture and of the Company/Undertaking****1.1 Product identifier**

- Product Name** • **C-Cement**
Product Code • 80802377 (98-680); 80805238 (98-681); 80806201 (98-682)

1.2 Relevant identified uses of the substance or mixture and uses advised against

- Relevant identified use(s)** • Adhesive

1.3 Details of the supplier of the safety data sheet

- Manufacturer** • Patch Rubber Company
100 Patch Rubber Road
Weldon, NC 27890
United States
- Telephone (General)** • (252)-536-2574
- Responsible party** • Christian Gimenez
Intertek Analytical Services France
France

Telephone (Technical) • 33 (0) 6 07 11 22 15

1.4 Emergency telephone number

- Manufacturer** • 1-800-424-9300 - CHEMTREC
Manufacturer • +1 703-527-3887 - CHEMTREC - Outside USA & CANADA (collect calls accepted)

Section 2: Hazards Identification**EU/EEC**

According to EU Directive 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]

According to EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

2.1 Classification of the substance or mixture

- CLP** • Flammable Liquids 2 - H225
Skin Irritation 2 - H315
Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336
Hazardous to the aquatic environment Acute 1 - H400
Hazardous to the aquatic environment Chronic 1 - H410
- DSD/DPD** • Highly Flammable (F)

Irritant (Xi)
 Harmful (Xn)
 Dangerous to the Environment (N)
 R11, R38, R50, R53, R67

2.2 Label Elements

CLP

DANGER



- Hazard statements**
- H225 - Highly flammable liquid and vapour
 - H315 - Causes skin irritation
 - H336 - May cause drowsiness or dizziness
 - H400 - Very toxic to aquatic life
 - H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements

- Prevention**
- P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
 - P273 - Avoid release to the environment.
 - P280 - Wear protective gloves/protective clothing/eye protection/face protection.
- Response**
- P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 - P331 - Do NOT induce vomiting.
- Storage/Disposal**
- P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

DSD/DPD



- Risk phrases**
- R11 - Highly flammable.
 - R38 - Irritating to skin.
 - R67 - Vapours may cause drowsiness and dizziness.
 - R50 - Very toxic to aquatic organisms.
 - R53 - May cause long-term adverse effects in the aquatic environment.
- Safety phrases**
- S2 - Keep out of reach of children.
 - S9 - Keep container in a well ventilated place
 - S16 - Keep away from sources of ignition - No Smoking.
 - S29 - Do not empty into drains.
 - S33 - Take precautionary measures against static discharges.
 - S60 - This material and its container must be disposed of as hazardous waste.
 - S61 - Avoid release to the environment. Refer to special instructions/ Safety Data Sheets.
 - S62 - If swallowed, do not induce vomiting. Seek medical advice immediately and show the container or label.

2.3 Other Hazards

CLP

- According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.
 This material contain less than 0.1% Benzene therefore the carcinogen and mutagen classifications listed in Annex VI are not applicable.

DSD/DPD

- According to European Directive 1999/45/EC this preparation is not considered dangerous.
 This material contain less than 0.1% Benzene therefore the carcinogen and mutagen classifications listed in Annex I are not applicable.

United States (US) According to OSHA GHS

2.1 Classification of the substance or mixture

OSHA HCS 2012

- Flammable Liquids 2 - H225
- Skin Irritation 2 - H315
- Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336

2.2 Label elements

OSHA HCS 2012

DANGER



- Hazard statements**
- Highly flammable liquid and vapour - H225
 - Causes skin irritation - H315
 - May cause drowsiness or dizziness - H336

Precautionary statements

- Prevention**
- Keep away from heat, sparks, open flames and/or hot surfaces. - P210
 - Keep container tightly closed. - P233
 - Keep cool. - P235
 - Ground and/or bond container and receiving equipment. - P240
 - Use explosion-proof - electrical, ventilating and/or lighting equipment. - P241
 - Use only non-sparking tools. - P242
 - Take precautionary measures against static discharge. - P243
 - Avoid breathing dust, fume, gas, mist, vapours and/or spray. - P261
 - Wash thoroughly after handling. - P264
 - Use only outdoors or in a well-ventilated area. - P271
 - Wear protective gloves/protective clothing/eye protection/face protection. - P280
- Response**
- In case of fire: Use appropriate media for extinction. - P370+P378
 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. - P304+P340
 - Call a POISON CENTER or doctor/physician if you feel unwell. - P312
 - IF ON SKIN: Wash with plenty of soap and water. - P302+P352
 - Rinse skin with water/shower. - P353
 - Take off contaminated clothing and wash before reuse. - P362
 - If skin irritation occurs: Get medical advice/attention. - P332+P313
 - Specific treatment, see supplemental first aid information. - P321
- Storage/Disposal**
- Dispose of content and/or container in accordance with local, regional, national, and/or international regulations. - P501
 - Store in a well-ventilated place. Keep container tightly closed. - P403+P233

2.3 Other hazards

OSHA HCS 2012

- Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

Canada

According to WHMIS

2.1 Classification of the substance or mixture

WHMIS

- Flammable Liquids - B2
- Other Toxic Effects - D2B

2.2 Label elements

WHMIS




- Flammable Liquids - B2
- Other Toxic Effects - D2B

2.3 Other hazards

WHMIS

- In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).
-

2.4 Other information



See Section 12 for Ecological Information.